

# Kettenspanner Chain Tensioner



Simplex | simplex  
automatisch nachspannend | automatic tensioner  
mit Kettenrad | with sprocket

ISO-No.	* p [inch]	[mm]	ZZ	S <sub>max</sub>	d	d <sub>n</sub>	H	E	V	R	K	U	J <sub>1</sub>	J <sub>2</sub>	G	N	O	W	[kg]	Bestell Nr. Part No.	
06 B-1	3/8	9,525	15	50	45,81	58	M10	79 <sup>+1,5</sup> <sub>-0,5</sub>	85	34-	55	30	23	100	80	6	35	10,5	M10	0,75	381-101-003
08 B-1	1/2	12,7	15	50	61,08	58	M10	79 <sup>+1,5</sup> <sub>-0,5</sub>	85	34-	55	30	23	100	80	6	35	10,5	M10	0,80	381-201-003
10 B-1	5/8	15,875	15	65	76,35	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	42-	80	50	27	130	100	7	52	15	M12	2,05	381-301-009
12 B-1	3/4	19,05	15	65	91,63	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	42-	80	50	27	130	100	7	52	15	M12	2,25	381-401-009
16 B-1	1	25,4	13	88	106,14	95	M16	140 <sup>+2</sup> <sub>-0,5</sub>	153	60-	100	60	40	175	140	10	66	15	M20	4,80	381-501-014
20 B-1	1 1/4	31,75	13	113	132,67	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	105-	142	70	100	225	180	12	80	18	M20	8,40	381-601-023
24 B-1	1 1/2	38,1	11	113	135,23	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	90-	160	70	70	225	180	12	80	18	M20	8,75	381-701-023

Duplex | duplex  
automatisch nachspannend | automatic tensioner  
mit Kettenrad | with sprocket

ISO-No.	* p [inch]	[mm]	ZZ	S <sub>max</sub>	d	d <sub>n</sub>	H	E	V	R	K	U	J <sub>1</sub>	J <sub>2</sub>	G	N	O	W	[kg]	Bestell Nr. Part No.	
06 B-2	3/8	9,525	15	50	45,81	58	M10	79 <sup>+1,5</sup> <sub>-0,5</sub>	85	43-	54	30	23	100	80	6	35	10,5	M10	0,80	381-102-003
08 B-2	1/2	12,7	15	50	61,08	58	M10	79 <sup>+1,5</sup> <sub>-0,5</sub>	85	47-	54	30	23	100	80	6	35	10,5	M10	0,95	381-202-003
10 B-2	5/8	15,875	15	65	76,35	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	58-	78	50	27	130	100	7	52	15	M12	2,30	381-302-009
12 B-2	3/4	19,05	15	65	91,63	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	61-	80	50	27	130	100	7	52	15	M12	2,75	381-402-009
16 B-2	1	25,4	13	88	106,14	95	M16	140 <sup>+2</sup> <sub>-0,5</sub>	153	69-	98	60	20	175	140	10	66	15	M20	5,65	381-502-014
20 B-2	1 1/4	31,75	13	113	132,67	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	123-	156	70	70	225	180	12	80	18	M20	10,00	381-602-023
24 B-2	1 1/2	38,1	11	113	135,23	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	132-	154	70	70	225	180	12	80	18	M20	10,65	381-702-023

Triplex | triplex  
automatisch nachspannend | automatic tensioner  
mit Kettenrad | with sprocket

ISO-No.	* p [inch]	[mm]	ZZ	S <sub>max</sub>	d	d <sub>n</sub>	H	E	V	R	K	U	J <sub>1</sub>	J <sub>2</sub>	G	N	O	W	[kg]	Bestell Nr. Part No.	
06 B-3	3/8	9,525	15	50	45,81	58	M10	79 <sup>+1,5</sup> <sub>-0,5</sub>	85	40-	55	30	8	100	80	6	35	10,5	M10	0,85	381-103-003
08 B-3	1/2	12,7	15	65	61,08	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	69-	79	50	27	130	100	7	52	15	M12	2,20	381-203-009
10 B-3	5/8	15,875	15	65	76,35	78	M12	108 <sup>+2</sup> <sub>-0,5</sub>	115	73-	80	50	27	130	100	7	52	15	M12	2,60	381-303-009
12 B-3	3/4	19,05	15	88	91,63	95	M16	140 <sup>+2</sup> <sub>-0,5</sub>	153	79-	100	60	20	175	140	10	66	15	M20	5,05	381-403-014
16 B-3	1	25,4	13	113	106,14	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	117-	151	70	40	225	180	12	80	18	M20	9,30	381-503-023
20 B-3	1 1/4	31,75	13	113	132,67	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	130-	153	70	40	225	180	12	80	18	M20	11,60	381-603-023
24 B-3	1 1/2	38,1	11	113	135,23	115	M20	200 <sup>+3</sup> <sub>-1</sub>	210	127-	148	70	20	225	180	12	80	18	M20	12,60	381-703-023

\* ZZ: Zähnezahl | no. of teeth

\* p = Kettenteilung | chain pitch